

4½ in 15.1 lb/ft TX22-125 (S31803)**Box end finish: Cu-Plating Lubrication: API-Modified****Clearance: Standard Bevel: 45°****PIPE BODY CHARACTERISTICS**

| | |
|------------------------|----------|
| Nominal OD | 4.500 in |
| Nominal ID | 3.826 in |
| Min. Yield Strength | 125 ksi |
| Nominal Wall Thickness | 0.337 in |
| Minimum Wall Thickness | 90 % |
| Drift | 3.701 in |

CONNECTION PROPERTIES

| | |
|------------------------------|---------------|
| Coupling OD (nominal) | 5.043 in |
| Coupling ID (nominal) | 3.818 in |
| Make-up Loss | 3.342 in |
| Coupling Length | 7.441 in |
| Tension Efficiency | 100 % of pipe |
| Compression Efficiency | 100 % of pipe |
| Internal Pressure Efficiency | 100 % of pipe |
| External Pressure Efficiency | 100 % of pipe |

CONNECTION PERFORMANCE

| | |
|-----------------------------------|-------------|
| Tensile Yield Load | 551 klb |
| Compression Yield Load | 441 klb |
| Internal Yield Pressure | 16 850 psi |
| External Pressure Resistance | 15 830 psi |
| Max. Bending with API Sealability | 20 °/100 ft |
| Max. Load on Coupling Face | 270 klb |

TORQUE VALUES

| | |
|----------------------------|-------------|
| Minimum Make-up torque | 6 900 ft·lb |
| Optimum Make-up torque | 7 670 ft·lb |
| Maximum Make-up torque | 8 440 ft·lb |
| Minimum Shoulder Torque | 380 ft·lb |
| Maximum Shoulder Torque | 5 370 ft·lb |
| Maximum Operational Torque | 9 200 ft·lb |

Connection qualified as per ISO 13679:2002 - CAL IVwww.sentinelconnections.com

PCTDS-SENTINEL_One-4.5-15.1-TX22-125

Date of issue (dd/mm/yyyy): 07/02/2025

TUBACEX
GROUP