

4½ in 12.6 lb/ft TX28-110 (N08028)**Box end finish: Cu-Plating Lubrication: API-Modified****Clearance: Standard Bevel: 45°****PIPE BODY CHARACTERISTICS**

Nominal OD	4.500 in
Nominal ID	3.958 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.271 in
Minimum Wall Thickness	90 %
Drift	3.833 in

CONNECTION PROPERTIES

Coupling OD (nominal)	4.937 in
Coupling ID (nominal)	3.913 in
Make-up Loss	3.342 in
Coupling Length	7.441 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	396 klb
Compression Yield Load	317 klb
Internal Yield Pressure	11 920 psi
External Pressure Resistance	9 210 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	166 klb

TORQUE VALUES

Minimum Make-up torque	4 650 ft·lb
Optimum Make-up torque	5 160 ft·lb
Maximum Make-up torque	5 680 ft·lb
Minimum Shoulder Torque	260 ft·lb
Maximum Shoulder Torque	3 610 ft·lb
Maximum Operational Torque	6 200 ft·lb

Connection qualified as per ISO 13679:2002 - CAL IVwww.sentinelconnections.com

PCTDS-SENTINEL_One-4.5-12.6-TX28-110

Date of issue (dd/mm/yyyy): 07/02/2025

TUBACEX
GROUP