

5½ in 20 lb/ft TX28-110 (N08028)**Box end finish: Cu-Plating Lubrication: API-Modified****Clearance: Standard Bevel: 45°****PIPE BODY CHARACTERISTICS**

Nominal OD	5.500 in
Nominal ID	4.778 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.361 in
Minimum Wall Thickness	90 %
Drift	4.653 in

CONNECTION PROPERTIES

Coupling OD (nominal)	6.071 in
Coupling ID (nominal)	4.785 in
Make-up Loss	4.413 in
Coupling Length	10.748 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	641 klb
Compression Yield Load	513 klb
Internal Yield Pressure	13 000 psi
External Pressure Resistance	11 100 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	263 klb

TORQUE VALUES

Minimum Make-up torque	9 760 ft·lb
Optimum Make-up torque	10 840 ft·lb
Maximum Make-up torque	11 930 ft·lb
Minimum Shoulder Torque	550 ft·lb
Maximum Shoulder Torque	7 590 ft·lb
Maximum Operational Torque	13 010 ft·lb

Connection qualified as per ISO 13679:2002 - CAL IVwww.sentinelconnections.com

PCTDS-SENTINEL_One-5.5-20-TX28-110

Date of issue (dd/mm/yyyy): 07/02/2025

TUBACEX
GROUP