

**7 in 32 lb/ft TX28-125 (N08028)****Box end finish: Cu-Plating Lubrication: API-Modified****Clearance: Standard Bevel: 45°****PIPE BODY CHARACTERISTICS**

|                        |          |
|------------------------|----------|
| Nominal OD             | 7.000 in |
| Nominal ID             | 6.094 in |
| Min. Yield Strength    | 125 ksi  |
| Nominal Wall Thickness | 0.453 in |
| Minimum Wall Thickness | 90 %     |
| Drift                  | 6.000 in |

**CONNECTION PROPERTIES**

|                              |               |
|------------------------------|---------------|
| Coupling OD (nominal)        | 7.744 in      |
| Coupling ID (nominal)        | 6.050 in      |
| Make-up Loss                 | 4.761 in      |
| Coupling Length              | 11.535 in     |
| Tension Efficiency           | 100 % of pipe |
| Compression Efficiency       | 100 % of pipe |
| Internal Pressure Efficiency | 100 % of pipe |
| External Pressure Efficiency | 100 % of pipe |

**CONNECTION PERFORMANCE**

|                                   |             |
|-----------------------------------|-------------|
| Tensile Yield Load                | 1 165 klb   |
| Compression Yield Load            | 932 klb     |
| Internal Yield Pressure           | 14 560 psi  |
| External Pressure Resistance      | 11 710 psi  |
| Max. Bending with API Sealability | 20 °/100 ft |
| Max. Load on Coupling Face        | 606 klb     |

**TORQUE VALUES**

|                            |              |
|----------------------------|--------------|
| Minimum Make-up torque     | 20 840 ft·lb |
| Optimum Make-up torque     | 23 160 ft·lb |
| Maximum Make-up torque     | 25 480 ft·lb |
| Minimum Shoulder Torque    | 1 160 ft·lb  |
| Maximum Shoulder Torque    | 16 210 ft·lb |
| Maximum Operational Torque | 27 790 ft·lb |

**Connection qualified as per ISO 13679:2002 - CAL IV**[www.sentinelconnections.com](http://www.sentinelconnections.com)

PCTDS-SENTINEL\_One-7-32-TX28-125

Date of issue (dd/mm/yyyy): 07/02/2025

**TUBACEX**  
GROUP