

7 in 32 lb/ft L80 13Cr (API 5CT)

Box end finish: Cu-Plating Lubrication: API-Modified
Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	7.000 in
Nominal ID	6.094 in
Min. Yield Strength	80 ksi
Nominal Wall Thickness	0.453 in
Minimum Wall Thickness	87.5 %
Drift	6.000 in

CONNECTION PROPERTIES

Coupling OD (nominal)	7.744 in
Coupling ID (nominal)	6.054 in
Make-up Loss	4.761 in
Coupling Length	11.535 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	746 klb
Compression Yield Load	746 klb
Internal Yield Pressure	9 060 psi
External Pressure Resistance	8 600 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	485 klb

TORQUE VALUES

Minimum Make-up torque	15 000 ft·lb
Optimum Make-up torque	16 670 ft·lb
Maximum Make-up torque	18 340 ft·lb
Minimum Shoulder Torque	830 ft·lb
Maximum Shoulder Torque	11 670 ft·lb
Maximum Operational Torque	20 000 ft·lb

Connection qualified as per ISO 13679:2002 - CAL IV

