

## 5 in 21.4 lb/ft P110 (API 5CT)

**Box end finish: Mang. Phosph. Lubrication: API-Modified**

**Clearance: Standard Bevel: 45°**

### PIPE BODY CHARACTERISTICS

Nominal OD	5.000 in
Nominal ID	4.126 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.437 in
Minimum Wall Thickness	87.5 %
Drift	4.001 in

### CONNECTION PROPERTIES

Coupling OD (nominal)	5.691 in
Coupling ID (nominal)	4.069 in
Make-up Loss	4.191 in
Coupling Length	10.394 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

### CONNECTION PERFORMANCE

Tensile Yield Load	689 klb
Compression Yield Load	689 klb
Internal Yield Pressure	17 310 psi
External Pressure Resistance	17 550 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	432 klb

### TORQUE VALUES

Minimum Make-up torque	11 750 ft·lb
Optimum Make-up torque	13 050 ft·lb
Maximum Make-up torque	14 360 ft·lb
Minimum Shoulder Torque	660 ft·lb
Maximum Shoulder Torque	9 140 ft·lb
Maximum Operational Torque	15 670 ft·lb

**Connection qualified as per ISO 13679:2002 - CAL IV**



[www.sentinelconnections.com](http://www.sentinelconnections.com)

PCTDS-SENTINEL\_One-5-21.4-P110

Date of issue (dd/mm/yyyy): 30/04/2026

**TUBACEX**  
GROUP