

## 6<sup>5</sup>/<sub>8</sub> in 24 lb/ft P110 (API 5CT)

Box end finish: Mang. Phosph. Lubrication: API-Modified

Clearance: Standard Bevel: 45°

### PIPE BODY CHARACTERISTICS

Nominal OD	6.625 in
Nominal ID	5.921 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.352 in
Minimum Wall Thickness	87.5 %
Drift	5.796 in

### CONNECTION PROPERTIES

Coupling OD (nominal)	7.283 in
Coupling ID (nominal)	5.850 in
Make-up Loss	4.921 in
Coupling Length	10.866 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

### CONNECTION PERFORMANCE

Tensile Yield Load	763 klb
Compression Yield Load	763 klb
Internal Yield Pressure	10 520 psi
External Pressure Resistance	6 730 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	459 klb

### TORQUE VALUES

Minimum Make-up torque	13 010 ft·lb
Optimum Make-up torque	14 460 ft·lb
Maximum Make-up torque	15 900 ft·lb
Minimum Shoulder Torque	720 ft·lb
Maximum Shoulder Torque	10 120 ft·lb
Maximum Operational Torque	17 350 ft·lb

Connection qualified as per ISO 13679:2002 - CAL IV

