

7⁵/₈ in 29.7 lb/ft P110 (API 5CT)

Box end finish: Mang. Phosph. Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	7.625 in
Nominal ID	6.875 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.375 in
Minimum Wall Thickness	87.5 %
Drift	6.750 in

CONNECTION PROPERTIES

Coupling OD (nominal)	8.213 in
Coupling ID (nominal)	6.814 in
Make-up Loss	5.220 in
Coupling Length	11.732 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	939 klb
Compression Yield Load	939 klb
Internal Yield Pressure	9 740 psi
External Pressure Resistance	5 350 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	488 klb

TORQUE VALUES

Minimum Make-up torque	16 600 ft·lb
Optimum Make-up torque	18 440 ft·lb
Maximum Make-up torque	20 280 ft·lb
Minimum Shoulder Torque	920 ft·lb
Maximum Shoulder Torque	12 910 ft·lb
Maximum Operational Torque	22 130 ft·lb

Connection qualified as per ISO 13679:2002 - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_One-7.625-29.7-P110

Date of issue (dd/mm/yyyy): 30/04/2026

TUBACEX
GROUP