

## 7 in 26 lb/ft P110 (API 5CT)

**Box end finish: Mang. Phosph. Lubrication: API-Modified**  
**Clearance: Standard Bevel: 45°**

### PIPE BODY CHARACTERISTICS

Nominal OD	7.000 in
Nominal ID	6.276 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.362 in
Minimum Wall Thickness	87.5 %
Drift	6.151 in

### CONNECTION PROPERTIES

Coupling OD (nominal)	7.592 in
Coupling ID (nominal)	6.205 in
Make-up Loss	4.761 in
Coupling Length	11.535 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

### CONNECTION PERFORMANCE

Tensile Yield Load	830 klb
Compression Yield Load	830 klb
Internal Yield Pressure	10 240 psi
External Pressure Resistance	6 230 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	467 klb

### TORQUE VALUES

Minimum Make-up torque	14 940 ft·lb
Optimum Make-up torque	16 600 ft·lb
Maximum Make-up torque	18 250 ft·lb
Minimum Shoulder Torque	830 ft·lb
Maximum Shoulder Torque	11 620 ft·lb
Maximum Operational Torque	19 910 ft·lb

**Connection qualified as per ISO 13679:2002 - CAL IV**



[www.sentinelconnections.com](http://www.sentinelconnections.com)

PCTDS-SENTINEL\_One-7-26-P110

Date of issue (dd/mm/yyyy): 30/04/2026

**TUBACEX**  
GROUP