

## 5½ in 26.8 lb/ft Q125 (API 5CT)

**Box end finish: Mang. Phosph. Lubrication: API-Modified**  
**Clearance: Standard Bevel: 45°**

### PIPE BODY CHARACTERISTICS

Nominal OD	5.500 in
Nominal ID	4.500 in
Min. Yield Strength	125 ksi
Nominal Wall Thickness	0.500 in
Minimum Wall Thickness	87.5 %
Drift	4.375 in

### CONNECTION PROPERTIES

Coupling OD (nominal)	6.283 in
Coupling ID (nominal)	4.438 in
Make-up Loss	4.413 in
Coupling Length	10.748 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

### CONNECTION PERFORMANCE

Tensile Yield Load	982 klb
Compression Yield Load	982 klb
Internal Yield Pressure	20 450 psi
External Pressure Resistance	20 660 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	629 klb

### TORQUE VALUES

Minimum Make-up torque	18 250 ft·lb
Optimum Make-up torque	20 280 ft·lb
Maximum Make-up torque	22 310 ft·lb
Minimum Shoulder Torque	1 020 ft·lb
Maximum Shoulder Torque	14 200 ft·lb
Maximum Operational Torque	24 340 ft·lb

**Connection qualified as per ISO 13679:2002 - CAL IV**

