

**7<sup>5</sup>/<sub>8</sub> in 33.7 lb/ft Q125 (API 5CT)**

**Box end finish: Mang. Phosph. Lubrication: API-Modified**  
**Clearance: Standard Bevel: 45°**

**PIPE BODY CHARACTERISTICS**

Nominal OD	7.625 in
Nominal ID	6.765 in
Min. Yield Strength	125 ksi
Nominal Wall Thickness	0.430 in
Minimum Wall Thickness	87.5 %
Drift	6.640 in

**CONNECTION PROPERTIES**

Coupling OD (nominal)	8.305 in
Coupling ID (nominal)	6.704 in
Make-up Loss	5.220 in
Coupling Length	11.732 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

**CONNECTION PERFORMANCE**

Tensile Yield Load	1 215 klb
Compression Yield Load	1 215 klb
Internal Yield Pressure	12 690 psi
External Pressure Resistance	8 340 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	704 klb

**TORQUE VALUES**

Minimum Make-up torque	19 140 ft·lb
Optimum Make-up torque	21 260 ft·lb
Maximum Make-up torque	23 390 ft·lb
Minimum Shoulder Torque	1 060 ft·lb
Maximum Shoulder Torque	14 880 ft·lb
Maximum Operational Torque	25 520 ft·lb

**Connection qualified as per ISO 13679:2002 - CAL IV**



[www.sentinelconnections.com](http://www.sentinelconnections.com)

**PCTDS-SENTINEL\_One-7.625-33.7-Q125**  
**Date of issue (dd/mm/yyyy):** 30/04/2026

**TUBACEX**  
GROUP