

## 7 in 29 lb/ft Q125 (API 5CT)

**Box end finish: Mang. Phosph. Lubrication: API-Modified**

**Clearance: Standard Bevel: 45°**

### PIPE BODY CHARACTERISTICS

Nominal OD	7.000 in
Nominal ID	6.184 in
Min. Yield Strength	125 ksi
Nominal Wall Thickness	0.408 in
Minimum Wall Thickness	87.5 %
Drift	6.059 in

### CONNECTION PROPERTIES

Coupling OD (nominal)	7.671 in
Coupling ID (nominal)	6.113 in
Make-up Loss	4.761 in
Coupling Length	11.535 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

### CONNECTION PERFORMANCE

Tensile Yield Load	1 056 klb
Compression Yield Load	1 056 klb
Internal Yield Pressure	13 110 psi
External Pressure Resistance	9 110 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	648 klb

### TORQUE VALUES

Minimum Make-up torque	19 150 ft·lb
Optimum Make-up torque	21 270 ft·lb
Maximum Make-up torque	23 400 ft·lb
Minimum Shoulder Torque	1 060 ft·lb
Maximum Shoulder Torque	14 890 ft·lb
Maximum Operational Torque	25 530 ft·lb

**Connection qualified as per ISO 13679:2002 - CAL IV**



[www.sentinelconnections.com](http://www.sentinelconnections.com)

PCTDS-SENTINEL\_One-7-29-Q125

Date of issue (dd/mm/yyyy): 30/04/2026

**TUBACEX**  
GROUP