

7 in 32 lb/ft TXG50-110 (N06950)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	7.000 in
Nominal ID	6.094 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.453 in
Minimum Wall Thickness	90 %
Drift	6.000 in

CONNECTION PROPERTIES

Coupling OD (nominal)	7.744 in
Coupling ID (nominal)	6.054 in
Make-up Loss	4.761 in
Coupling Length	11.535 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	1 025 klb
Compression Yield Load	820 klb
Internal Yield Pressure	12 810 psi
External Pressure Resistance	10 780 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	533 klb

TORQUE VALUES

Minimum Make-up torque	18 920 ft·lb
Optimum Make-up torque	21 020 ft·lb
Maximum Make-up torque	23 120 ft·lb
Minimum Shoulder Torque	1 050 ft·lb
Maximum Shoulder Torque	14 710 ft·lb
Maximum Operational Torque	25 220 ft·lb

Connection qualified as per ISO 13679:2002 - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_One-7-32-TXG50-110

Date of issue (dd/mm/yyyy): 30/04/2026

TUBACEX
GROUP