

## Technical Datasheet

### 7 in 32 lb/ft L80 13Cr (API 5CT)

Clearance: Standard Bevel: 45°

#### PIPE BODY CHARACTERISTICS

Nominal OD	7.000 in
Nominal ID	6.094 in
Min. Yield Strength	80 ksi
Nominal Wall Thickness	0.453 in
Minimum Wall Thickness	87.5 %
Drift	6.000 in

#### CONNECTION PROPERTIES

Coupling OD (nominal)	7.732 in
Coupling ID (nominal)	6.055 in
Make-up Loss	4.954 in
Coupling Length	11.339 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

#### CONNECTION PERFORMANCE

Tensile Yield Load	746 klb
Compression Yield Load	746 klb
Internal Yield Pressure	9 060 psi
External Pressure Resistance	8 600 psi
Max. Bending with Sealability	38 °/100 ft
Max. Structural Bending	52 °/100 ft
Max. Load on Coupling Face	482 klb

#### TORQUE VALUES

Minimum Make-up torque	17 250 ft-lb
Optimum Make-up torque	19 170 ft-lb
Maximum Make-up torque	21 090 ft-lb
Minimum Shoulder Torque	960 ft-lb
Maximum Shoulder Torque	13 420 ft-lb
Maximum Operational Torque	24 280 ft-lb

Box end finish: Cu-Plating Pin end finish: As machined Lubrication: API-Modified



Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV

**TUBACEX**  
GROUP