

Technical Datasheet

4½ in 12.6 lb/ft Q125 (API 5CT)

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	4.500 in
Nominal ID	3.958 in
Min. Yield Strength	125 ksi
Nominal Wall Thickness	0.271 in
Minimum Wall Thickness	87.5 %
Drift	3.833 in

CONNECTION PROPERTIES

Coupling OD (nominal)	4.937 in
Coupling ID (nominal)	3.898 in
Make-up Loss	3.521 in
Coupling Length	7.913 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	450 klb
Compression Yield Load	450 klb
Internal Yield Pressure	13 550 psi
External Pressure Resistance	9 890 psi
Max. Bending with Sealability	66 °/100 ft
Max. Structural Bending	127 °/100 ft
Max. Load on Coupling Face	245 klb

TORQUE VALUES

Minimum Make-up torque	7 070 ft-lb
Optimum Make-up torque	7 860 ft-lb
Maximum Make-up torque	8 640 ft-lb
Minimum Shoulder Torque	390 ft-lb
Maximum Shoulder Torque	5 500 ft-lb
Maximum Operational Torque	8 640 ft-lb

Box end finish: Cu-Plating Pin end finish: As machined Lubrication: API-Modified



Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV

TUBACEX
GROUP