

Technical Datasheet

9⁵/₈ in 47 lb/ft S13Cr-95 (UNS S41425)

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	9.625 in
Nominal ID	8.681 in
Min. Yield Strength	95 ksi
Nominal Wall Thickness	0.472 in
Minimum Wall Thickness	87.5 %
Drift	8.525 in

CONNECTION PROPERTIES

Coupling OD (nominal)	10.502 in
Coupling ID (nominal)	8.632 in
Make-up Loss	5.487 in
Coupling Length	12.795 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	1 290 klb
Compression Yield Load	1 290 klb
Internal Yield Pressure	8 150 psi
External Pressure Resistance	5 090 psi
Max. Bending with Sealability	30 °/100 ft
Max. Structural Bending	45 °/100 ft
Max. Load on Coupling Face	900 klb

TORQUE VALUES

Minimum Make-up torque	26 910 ft-lb
Optimum Make-up torque	29 900 ft-lb
Maximum Make-up torque	32 890 ft-lb
Minimum Shoulder Torque	1 500 ft-lb
Maximum Shoulder Torque	20 930 ft-lb
Maximum Operational Torque	37 820 ft-lb

Box end finish: Cu-Plating Pin end finish: As machined Lubrication: API-Modified

