Technical Datasheet
4½ in 17 lb/ft TX22-125 (UNS S31803, 125 ksi)

Clearance: Standard Bevel: 45º



PIPE BODY CHARACTERISTICS

Nominal OD	4.500	in
Nominal ID	3.740	in
Min. Yield Strength	125	ksi
Min. Compression Yield Strength (80% asymmetry ratio)	100	ksi
Nominal Wall Thickness	0.380	in
Minimum Wall Thickness	90	%
Drift	3.615	in

CONNECTION PROPERTIES

Coupling OD (nominal)	5.128	in
Coupling ID (nominal)	3.680	in
Make-up Loss	3.521	in
Coupling Length	7.913	in
Tension Efficiency	100	% of pipe
Compression Efficiency	100	% of pipe
Internal Pressure Efficiency	100	% of pipe
External Pressure Efficiency	100	% of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	615	klb
Compression Yield Load	492	klb
Internal Yield Pressure	19 000	psi
External Pressure Resistance	19 330	psi
Max. Bending with Sealability	66	º/100 ft
Max. Structural Bending	115	º/100 ft
Max. Load on Coupling Face	346	klb

TORQUE VALUES

Minimum Make-up torque	11 340	ft·lb
Optimum Make-up torque	12 600	ft·lb
Maximum Make-up torque	13 860	ft·lb
Minimum Shoulder Torque	630	ft·lb
Maximum Shoulder Torque	8 820	ft·lb
Maximum Operational Torque	13 860	ft·lb

Box end finish: Cu-Plating Pin end finish: SS Bead Blasting Lubrication: API-Modified

Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV

sentinelconnections.com

TUBACEX GROUP

Tubacex's products and services are subject to the terms and conditions established by existing contracts or agreements.