

Technical Datasheet

5½ in 20 lb/ft TX25NP-80 (UNS S32750, 80 ksi)

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	5.500 in
Nominal ID	4.778 in
Min. Yield Strength	80 ksi
Min. Compression Yield Strength (80% asymmetry ratio)	64 ksi
Nominal Wall Thickness	0.361 in
Minimum Wall Thickness	87.5 %
Drift	4.653 in

CONNECTION PROPERTIES

Coupling OD (nominal)	6.098 in
Coupling ID (nominal)	4.711 in
Make-up Loss	4.535 in
Coupling Length	10.472 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	466 klb
Compression Yield Load	466 klb
Internal Yield Pressure	9 190 psi
External Pressure Resistance	8 830 psi
Max. Bending with Sealability	48 °/100 ft
Max. Structural Bending	67 °/100 ft
Max. Load on Coupling Face	282 klb

TORQUE VALUES

Minimum Make-up torque	6 970 ft-lb
Optimum Make-up torque	7 740 ft-lb
Maximum Make-up torque	8 520 ft-lb
Minimum Shoulder Torque	390 ft-lb
Maximum Shoulder Torque	5 420 ft-lb
Maximum Operational Torque	9 370 ft-lb

Box end finish: Cu-Plating Pin end finish: SS Bead Blasting Lubrication: API-Modified

