

## Technical Datasheet

### 5½ in 23 lb/ft TX28-125 (UNS N08028, 125 ksi)

Clearance: Standard Bevel: 45°

#### PIPE BODY CHARACTERISTICS

Nominal OD	5.500 in
Nominal ID	4.670 in
Min. Yield Strength	125 ksi
Min. Compression Yield Strength (80% asymmetry ratio)	100 ksi
Nominal Wall Thickness	0.415 in
Minimum Wall Thickness	90 %
Drift	4.545 in

#### CONNECTION PROPERTIES

Coupling OD (nominal)	6.181 in
Coupling ID (nominal)	4.603 in
Make-up Loss	4.535 in
Coupling Length	10.472 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

#### CONNECTION PERFORMANCE

Tensile Yield Load	829 klb
Compression Yield Load	663 klb
Internal Yield Pressure	16 980 psi
External Pressure Resistance	16 060 psi
Max. Bending with Sealability	58 °/100 ft
Max. Structural Bending	94 °/100 ft
Max. Load on Coupling Face	430 klb

#### TORQUE VALUES

Minimum Make-up torque	10 780 ft-lb
Optimum Make-up torque	11 980 ft-lb
Maximum Make-up torque	13 170 ft-lb
Minimum Shoulder Torque	600 ft-lb
Maximum Shoulder Torque	8 390 ft-lb
Maximum Operational Torque	14 490 ft-lb

**Box end finish: Cu-Plating Pin end finish: SS Bead Blasting Lubrication: API-Modified**

