

## Technical Datasheet

### 7 in 32 lb/ft TX825-110 (UNS N08825, 110 ksi)

Clearance: Standard Bevel: 45°

#### PIPE BODY CHARACTERISTICS

Nominal OD	7.000 in
Nominal ID	6.094 in
Min. Yield Strength	110 ksi
Min. Compression Yield Strength (80% asymmetry ratio)	88 ksi
Nominal Wall Thickness	0.453 in
Minimum Wall Thickness	90 %
Drift	6.000 in

#### CONNECTION PROPERTIES

Coupling OD (nominal)	7.732 in
Coupling ID (nominal)	6.055 in
Make-up Loss	4.954 in
Coupling Length	11.339 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

#### CONNECTION PERFORMANCE

Tensile Yield Load	1 025 klb
Compression Yield Load	820 klb
Internal Yield Pressure	12 810 psi
External Pressure Resistance	10 780 psi
Max. Bending with Sealability	42 °/100 ft
Max. Structural Bending	65 °/100 ft
Max. Load on Coupling Face	531 klb

#### TORQUE VALUES

Minimum Make-up torque	21 760 ft-lb
Optimum Make-up torque	24 170 ft-lb
Maximum Make-up torque	26 590 ft-lb
Minimum Shoulder Torque	1 210 ft-lb
Maximum Shoulder Torque	16 920 ft-lb
Maximum Operational Torque	27 080 ft-lb

**Box end finish: Cu-Plating Pin end finish: SS Bead Blasting Lubrication: API-Modified**



Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV

sentinelconnections.com

**TUBACEX**  
GROUP