

**Technical Datasheet**

**9<sup>5</sup>/<sub>8</sub> in 53.5 lb/ft TX825-110 (UNS N08825, 110 ksi)**

**Clearance: Standard Bevel: 45°**

**PIPE BODY CHARACTERISTICS**

Nominal OD	9.625 in
Nominal ID	8.535 in
Min. Yield Strength	110 ksi
Min. Compression Yield Strength (80% asymmetry ratio)	88 ksi
Nominal Wall Thickness	0.545 in
Minimum Wall Thickness	90 %
Drift	8.500 in

**CONNECTION PROPERTIES**

Coupling OD (nominal)	10.610 in
Coupling ID (nominal)	8.555 in
Make-up Loss	5.487 in
Coupling Length	12.795 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

**CONNECTION PERFORMANCE**

Tensile Yield Load	1 710 klb
Compression Yield Load	1 368 klb
Internal Yield Pressure	11 210 psi
External Pressure Resistance	7 950 psi
Max. Bending with Sealability	30 °/100 ft
Max. Structural Bending	47 °/100 ft
Max. Load on Coupling Face	991 klb

**TORQUE VALUES**

Minimum Make-up torque	43 290 ft-lb
Optimum Make-up torque	46 800 ft-lb
Maximum Make-up torque	50 310 ft-lb
Minimum Shoulder Torque	2 340 ft-lb
Maximum Shoulder Torque	33 930 ft-lb
Maximum Operational Torque	53 820 ft-lb

**Box end finish: Cu-Plating Pin end finish: SS Bead Blasting Lubrication: API-Modified**



**Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV**

sentinelconnections.com