

Technical Datasheet

3½ in 9.2 lb/ft TXG3-110 (UNS N06985, 110 ksi)

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	3.500 in
Nominal ID	2.992 in
Min. Yield Strength	110 ksi
Min. Compression Yield Strength (80% anisotropy ratio)	88 ksi
Nominal Wall Thickness	0.254 in
Minimum Wall Thickness	90 %
Drift	2.867 in

CONNECTION PROPERTIES

Coupling OD (nominal)	3.929 in
Coupling ID (nominal)	2.922 in
Make-up Loss	3.325 in
Coupling Length	7.362 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	285 klb
Compression Yield Load	228 klb
Internal Yield Pressure	14 370 psi
External Pressure Resistance	13 530 psi
Max. Bending with Sealability	42 °/100 ft
Max. Structural Bending	130 °/100 ft
Max. Load on Coupling Face	136 klb

TORQUE VALUES

Minimum Make-up torque	3 420 ft·lb
Optimum Make-up torque	3 810 ft·lb
Maximum Make-up torque	4 190 ft·lb
Minimum Shoulder Torque	190 ft·lb
Maximum Shoulder Torque	2 660 ft·lb
Maximum Operational Torque	4 190 ft·lb

Box end finish: Cu-Plating Pin end finish: SS Bead Blasting Lubrication: API-Modified

