

**Technical Datasheet**  
**7 in 26 lb/ft TXG50-110 (UNS N06950, 110 ksi)**  
Clearance: Standard Bevel: 45°

**PIPE BODY CHARACTERISTICS**

Nominal OD	7.000 in
Nominal ID	6.276 in
Min. Yield Strength	110 ksi
Min. Compression Yield Strength (80% asymmetry ratio)	88 ksi
Nominal Wall Thickness	0.362 in
Minimum Wall Thickness	90 %
Drift	6.151 in

**CONNECTION PROPERTIES**

Coupling OD (nominal)	7.583 in
Coupling ID (nominal)	6.211 in
Make-up Loss	4.954 in
Coupling Length	11.339 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

**CONNECTION PERFORMANCE**

Tensile Yield Load	830 klb
Compression Yield Load	664 klb
Internal Yield Pressure	10 240 psi
External Pressure Resistance	6 230 psi
Max. Bending with Sealability	42 °/100 ft
Max. Structural Bending	65 °/100 ft
Max. Load on Coupling Face	373 klb

**TORQUE VALUES**

Minimum Make-up torque	17 180 ft-lb
Optimum Make-up torque	19 080 ft-lb
Maximum Make-up torque	20 990 ft-lb
Minimum Shoulder Torque	950 ft-lb
Maximum Shoulder Torque	13 360 ft-lb
Maximum Operational Torque	22 070 ft-lb

**Box end finish: Cu-Plating Pin end finish: SS Bead Blasting Lubrication: API-Modified**

